



## Husqvarna K 970 Chain

*The K 970 Chain can make 390 mm cuts from one side. It can make openings as small as 110 mm x 110 mm, so it is perfect for irregularly shaped openings. The power-to-weight ratio is first rate and features SmartCarb™, a built-in automatic filter compensation and a highly efficient vibration dampening system. The K 970 Chain is also equipped with an X-Torq® engine, which reduces emissions up to 75 % and lowers fuel consumption by 20 % and DuraStarter™, a dust-sealed starter that boosts reliability and product life. Air Purge and a decompression valve make it very easy to start.*



### THE K 970 CHAIN

The K 970 Chain can make openings as small as 4-1/2" x 4-1/2", and is perfect for openings with irregular shapes.



### SMARTCARB™

Built-in automatic filter compensation, maintains high power and lowers fuel consumption.



### DURASTARTER™

Patented, dust sealed starter unit with a sealed return spring and pulley bearing. DuraStarter™ also includes a starter cord with greatly increased durability. This makes the starter virtually maintenance free, further enhancing the reliability of our cutters.



### ANTI-VIBRATION SYSTEM

Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position reduced strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.

## Features Husqvarna K 970 Chain

- Engine with X-Torq® produces 70 % less emissions, 20 % lower fuel consumption and more power.
- Makes up to 16" deep cuts from one side.
- Make up to 15" deep cuts from one side.
- Active Air Filtration, centrifugal air cleaning in three stages, extends product life and service intervals.
- Engine with X-Torq produces more power, higher torque and greatly reduced emissions.
- SmartCarb, built-in automatic filter compensation, maintains high power and lowers fuel consumption.
- DuraStarter, a dust-sealed starter, and the durable starter cord reduce the risk of downtime and increase reliability and service life.

| TECHNICAL SPECIFICATION               |                            |
|---------------------------------------|----------------------------|
| Engine                                | Air-cooled 2 stroke engine |
| Cylinder displacement                 | 5.71 cu.inch               |
| Power output                          | 6.5 hp                     |
| Fuel tank volume                      | 33.8 fl oz                 |
| Idling speed                          | 2700 rpm                   |
| Vibrations front handle               | 3.6 m/s <sup>2</sup>       |
| Vibrations rear handle                | 2.3 m/s <sup>2</sup>       |
| Sound pressure level at operators ear | 103 dB(A)                  |
| Sound power level, guaranteed (LWA)   | 116 dB(A)                  |
| Bar length                            | 14 inch                    |
| Max cutting depth                     | 15 inch                    |
| Weight (excl. cutting equipment)      | 20.9 lbs                   |
| Fuel tank volume                      | 2.1 US pint                |

